

## Klassische Keilriemen nach DIN 2215

Profil 5 x 3 mm Innenlänge (Li) mm
160
185
190
229
236
260
265
270
280
287
300
303
315
322
330
335
340
345
350
352
375
400
406
420
425
435
441
465
475
500
514
530
554
600


Profil 6 x 4 mm Innenlänge (li) mm
240
250
260
265
270
280
300
330
335
339
350
352
375
380
400
425
450
500
540
550
560
580
600
640
850
900

**Differenz:  
Innenlänge / Aussenlänge  
= 25 mm**

Profil 8 x 5 mm Innenlänge (li) mm	
280	680
315	700
335	710
340	725
355	750
365	775
375	800
385	825
400	830
425	850
430	875
450	900
475	950
490	965
500	1000
530	1020
545	1050
560	1075
575	1115
580	1120
600	1200
630	1250
650	1500
670	1545

**Differenz:  
Innenlänge / Aussenlänge  
= 32 mm**

**Differenz:  
Innenlänge / Aussenlänge  
= 19 mm**



## Klassische Keilriemen nach DIN 2215

Profil 20 x 12.5 mm Innenlänge (Li) mm		
770	1825	3900
800	1850	4000
900	1875	4100
925	1900	4250
950	1925	4300
975	1950	4500
1000	2000	4572
1030	2050	4750
1060	2060	5000
1120	2120	5300
1150	2150	5350
1180	2200	5450
1200	2240	5500
1215	2275	5600
1250	2330	5765
1275	2360	6000
1300	2415	6120
1320	2500	6300
1350	2600	6700
1360	2650	7100
1375	2675	7500
1400	2740	8000
1425	2800	
1450	2850	
1500	2900	
1525	2950	
1550	3000	
1565	3150	
1600	3250	
1650	3350	
1660	3450	
1700	3550	
1750	3650	
1775	3750	
1800	3850	

Profil 25 x 16 mm Innenlänge (li) mm	
1300	3250
1350	3350
1375	3400
1400	3450
1450	3550
1475	3595
1500	3650
1575	3750
1600	3795
1665	3880
1700	3950
1800	4000
1850	4100
1875	4250
1900	4450
1950	4500
2000	4750
2120	5000
2150	5300
2200	5600
2240	5800
2325	6000
2360	6300
2415	6500
2450	6700
2500	7100
2540	7350
2620	7500
2650	8000
2700	8500
2800	9000
2950	9250
3000	9500
3075	10000
3150	10400

**Differenz:**  
Innenlänge / Aussenlänge  
= 79 mm

**Differenz:**  
Innenlänge / Aussenlänge  
= 101 mm